

e)

	PLACE TYPES ▶	P2	P3	P4	P5	SPECIFICATIONS ▼
MARQUEE SIGNS					P	<ul style="list-style-type: none"> a. Quantity: 1 per Business max. b. Area: n/a c. Width: entrance plus 2 ft each side d. Height: 50% Story Height max. e. Depth / Projection: 4 ft min.; 10 ft max. f. Clearance: 10 ft min g. Apex: n/a h. Letter Height: n/a i. Distance from Curb: 3 ft min.
DESCRIPTION	<p>Marquees shall be located only above the Principal Entrance of a Building, shall provide a minimum clearance of 10 feet, and may Encroach the Public Frontage to within 2 feet of the Curb. Message Boards shall be permitted as part of Marquees.</p>					
SIGN DETAILS	<ul style="list-style-type: none"> i. Marquees shall be located only above the Principal Entrance of a Building. ii. No Marquee shall be wider than the entrance it serves, plus 2 feet on each side thereof. iii. No portion of a Marquee shall be lower than 10 feet Clearance. iv. No Marquee shall extend closer to the Curb than 3 feet. v. Columns or posts may be used as supports for Marquees 8 feet deep or deeper if approved by the DRC. vi. All Marquees, including anchors, bolts, supporting rods, and braces, shall be constructed of non-combustible materials and shall be designed by a structural engineer submitted for approval to the Building Official. vii. Marquee components and materials may vary. Anchors, bolts, and supporting rods should be limited to the interior of the Marquee. viii. Message Boards shall be permitted as part of Marquees. ix. A Band Sign shall be permitted above a Marquee. 					